



Aerosal Spray Paints / Enamels / Premium Enamels / Epoxy Paints / P. U. Paints / Hammertones / Poly chromatic Finish / Powder Coatings / Red Oxide Primers / Zinc Chrome Primers / F. D. Black.

www.kerolpaints.com







contact@kerolpaints.com

Kerol paints Unit No 2, Nirmal Industrial Co-Op society Ltd, Next to V.V.F. Ltd, Opp Sion Fort, Sion East Mumbai 400022

Company Phone No: 022 2404 2334 / 022 2403 7717 / 9768717022

ABOUT US:

Kerol paints are the Manufacturer and supplier of Industrial and decorative paints for more than 30 years. The process of this Evolution and growth began in 1985. Our performance is anchored today in a variety of decorative and industrial paints which continue to gain an increasing share of the highly competitive indian market, we provide tailor-made paints to the customer's requirement. We have a distribution network of 500 well reputed retailers to reach every corner of Maharashtra and Mumbai. Our production team is managed by experienced, qualified paint chemists and engineers. All batches of finished products are individually tested and passed by the in-house paints application laboratory before release. We also manufacture decorative and industrial water based paints under Brand name of Flexiguard. We pay highest regard to health and safety of those using our products and the environment in which they live and work. We at Kerol Paints, monitor our service levels closely; from order handling to speed of delivering material, everything we do is carefully measured and recorded. What we do is setting standards for ourselves, meeting them and than surpassing them. we are seen as the company that gets it right!

Flexiguard Acrylic Wall Putty

Flexiguard Acrylic Wall Putty is co-polymer base interior acrylic paste & powder form putty, which can be easily applied on plaster, gypsum or POP. The ingredients are carefully selected, which consist of best quality Sand, acrylic polymers, minerals, additives, anti-bacterial agents. It is smooth finish interior wall putty. It is Fungus & Bacteria resistance. It is a ready to use paste & powder form which can be easily applied with Putty Knife which is useful for consistent coating allover No priming required which saves the material & application cost of primer

Coverage: 15 - 18 sqft/kg for 2 coats on smooth surface

Packing Sizes: 1kg, 5kg, 20kg, 30kg





Flexiguard Cement Putty

Flexiguard Cement Putty which can be used to give the walls a smooth finish. It also fills up the holes & undulations existing in the substrate &can be used for External as well as Internal surfaces. Being water repellent it prevents seepage or dampness up to certain extent. As the mixture is co polymer is has good strength & high durability. It comes in two different finishes viz. coarse & fine. Being cement base it can be applied in thickness of 4-6mm in multiple coats depending upon the surface

Coverage: 12-14 sqft per kg for 2 coats on smooth surface, 7-8 sqft/kg for 2 coats on rough surface

Packing Sizes: 1kg, 5kg, 20kg, 40kg

Flexiguard Tex Designer Texture

Flexiguard Tex is an acrylic, semi viscous paste containing quartz, aggregates, acrylic polymers, minerals, specially formulated to withstand varying climate conditions &provide a long lasting elegant look to the surface. It also gives opportunity to create different designs. Textures can be used for interior as well as exterior walls. It imparts extra thickness to the surface making it water resistant. Very useful in hiding existing cracks undulations. Comes in different designs & thickness viz. Scratch, Roller, Bubble, Dholpur Coverage: 2-3 sqft/kg coat.

Packing Sizes: 25kg, 30kg



Flexiguard Exterior Wall Primer

Flexiguard exterior wall primer gives Excellent opacity and whiteness. Improves appearance of top coat. Does not chalk and can be applied on adequately cured fresh plaster. Does not require curing with water. Provides excellent adhesion to topcoat emulsions . Prevents peeling off of top coat emulsions

Coverage: 1 coat up to 120-140sqft/Ltr

Packing Sizes: 1L, 4L, 10L, 20L





Flexiguard Interior / Exterior Wall Primer

Flexiguard interior Wall primer can be thinned to application viscosity by adding appropriate amount of water. It's special features are easy brushing, excellent covering, alkali resistance, quick drying and good sealing properties. It is specially fortified with fungicides.

Coverage: I coat up to 225sqft/Ltr

Packing Sizes: 1L, 4L, 10L, 20L

Flexiguard Plus Acrylic Base Coat White

Flexiguard Plus Acrylic Base Coat White is a co-acrylic base primer which is specially formulated in a way that it can be used for both internal & external application. The contents of Flexiguard Plus are such that it gives the surface a smooth finish which is useful for internal application at the same time imparting opacity for external surface. It helps in reducing the consumption of the top coat as it substantially reduces the porosity of the substrate Flexiguard Plus is an economy product with high value additions

Coverage: On normal masonry surface brush applied: 110-130 sqft/Ltr coat depending upon the surface



Packing Sizes: 1L, 4L, 10L, 20L



Flexiguard Acrylic Distemper

Flexiguard Acrylic Distemper is co polymer water based interior wall finish that gives smooth finish to the walls. It is economical & low cost. Variety of shades can be developed having longer shade retention & smooth & matt finish

Coverage: The coverage on smooth primed masonry surface with the recommended application procedure is as follows:

Re - painting (2 coats): 55-85 sqft/kg New surface

(3 coats): 45 - 65 sqft/kg

Packing Sizes: 2kg, 5kg, 10kg, 20kg

Flexiguard Eon Interior Emulsion

Flexiguard Eon Interior Emulsion is the first upgradation from the distemper family. It is a co-polymer acrylic coating with better fungus resistance. It offers rich, elegant and smooth finish to walls & is much durable than distemper at a very marginal difference in cost.

Coverage: On smooth primed masonry surface by brushing 1 coat: 175-195 sqft./Ltr. or 2 coats: 130-150 sqft./Ltr.



Packing Sizes: 1L, 4L, 10L, 20L



Dzire Premium Interior Emulsion

Premium Quality Interior waterbased Acrylic copolymer emulsion based, top coat, pigmented with titanium dioxide and other high grade alkali resisting pigments. It delivers smooth finish. It has excellent scrub resistance and washability. It is resistance to fungus and Algae and is ideal for interior usage

Coverage: 190 to 200 Sq. Ft. per ltr.

Packing Sizes: 1L'4L'10L'20L



High Gloss Interior / Exterior Lustre Paint

High Gloss Lustre is a waterbased Interior / Exterior wall paint desinged to give wall premium Look with durability. It is specially formulated to provide Rich luster finish. The waterbased zinc can be added to and applied as "Dana Finish" or Smooth Finish.

Coverage: 100-120 Sq. Ft. / Ltr.. / 2 Coats for normal smooth finish.

Packing Sizes: 1L' 4L' 10L' 20L

Flexiguard Damp Proof

Flexiguard Damp Proof is a high strength fiber reinforced elostomeric Liquid water proofing coating.

It is formulated with elostomeric and resilient Acrylic Polymer, and reinforcing polyester fibre upon curing it forms a thick Seamless Durable membrane thus offering ultimate water proofing, which can over coated with premium Quality Exterior Paint.

Benefits: Upto 10-12% Surface Temperature reduction.

Upto 10 Years of water proofing.

Application: 1st Coat is self Priming Dilution by 30% of water.

2nd Coat Horizontal without dilution 3rd Coat Vertical without dilution.

Covrage: 15-17 Square Ft./ Ltr. for 3 Coat for Terrace.



Packing Sizes: 1L'4L'10L'20L



Flexiguard Eon Exterior Emulsion

Flexiguard Eon Exterior Emulsion is a water-based exterior wall finish with silicon additives suitable for dry to moderately humid climatic conditions. Eon offers excellent resistance to chalking, cracking and weathering in comparison to cement paint. Its modified acrylic binder ensures that paint stays on your wall longer than cement paint. Save Money in the Long Run Eon lasts longer than cement paint and hence proves more economical in the long run. It also does not require curing and therefore saves time, effort and money during application. Clean Shades and gives neat and clean shades that do not fade and last longer than cement paint shades. It is available in strong/dark shades that provide excellent hiding. Better Anti-algal Performance Coverage: 1 coat 110-130sqft/Ltr, 2 coat 55 - 65 sqft/Ltr

Packing Sizes: 1L, 4L, 10L, 20L

Flexiguard Prime Dust Proof Exterior Emulsion

Flexiguard prime Dust proof Exterior Emulsion is a high performance, long lasting and anti algae exterior paint specially formulated to withstand extreme tropical conditions of high rainfall, humidity and heat. It is based on a U.V. resistant acrylic binder and lightfast pigments. It has outstanding water resistant properties and excellent anti microbial properties, which prevent fungus and algal growth and helps in retaining the clean painted look year after year. Flexiguard primeWeatherproof Exterior Emulsion is an exterior wall finish that can be applied on various types of exterior cement plasters, exterior ceilings, asbestos sheets, concrete etc.

Coverage - 1 coat 110-130 sqft/Ltr, 2 coats 55-65 sqft/Ltr

Packing Sizes: 1L, 4L, 10L, 20L





Flexiguard Optima Weather Proof Exterior Emulsion

Flexiguard optima 100% Acrylic smooth emulsion with silicon additives that offers an anti-algal and high performance exterior wall finish. Flexiguard optima uses specially formulated high-performance color pigments and binder technology, which offer excellent resistance to uv radiation. This ensures brighter, shades that will not fade, ensure your home continues to look beautiful over time. Flexiguard optima comes with a comprehensive 7 year performance warranty*. (5 year warranty for coastal markets). Flexiguard optima contains an advanced Anti-algal Formula which fights the formation of algae and keeps away ugly black spots from your walls. Flexiguard optima is designed with a unique Dirt Pick Up Resistance (DPUR) property. It fights dust from settling on the wall surface and thereby retains theinitial beauty. Flexiguard optima offers excellent sheen, giving ur newly painted home a classy finish.

Coverage: 1 coat 110 - 130 sqft/Ltr, 2coat 55 - 65 Sqft/Ltr

Packing Sizes: 1L, 4L, 10L, 20L

Flexiguard Optima Max

Premium Exterior Waterproof Coating

Flexiguard Optima Max is premium exterior waterproof coating a superior exterior paint that will help you bid farewell to dampness, algae, cracks colour fading and fungus on wall. Optima Max premium exterior waterproof coating keeps wall looking vibrant even through the severe weather conditions-rains, dust or harsh sun. This advanced exterior paint, equipped with fibre technology, comes with a first of a kind ten years performance warranty for topcoat.

Coverage: 60 to 70 Sq. Ft./per Ltr. for 2 Coats.

Packing Sizes: 1L, 4L, 10L, 20L





Flexiguard Plus Dual Emulsion (Interior / Exterior)

Flexiguard Plus Dual Emulsion is a waterbased exterior interior wall finish with silicon additives suitable for dry to moderately humid climatic conditions. Flexiguard Plus offers excellent resistance to chalking, carcking and weathering in comparison to cement paint. Its modified acrylic binder ensures that paint stays on your wall longer than cement paint. Save Money in the Long Run Flexiguard Plus Dual Emulsions lasts longer than cement paint and hence proves more economical in the long run.

Coverage: 1 Coat 100-110 sq.ft./Ltr. 2 Coat 50-55 sq.ft/Ltr.

Packing Sizes: 1L' 4L' 10L' 20L

Kerol Multi Purpose Spray Paint

Kerol Multi Purpose Spray Paint can be used for industrial purpose & for Decorative purpose. It is formulated in such way to get the best coverage on walls and on metals. It can be used in all weather.







Kerol Leak Stop Spray

Kerol Leak Stop Spray Seal Leaks anywhere seal even the toughest leaks. Deeps into cracks and holes. Dries to a watertights, flexible, rubberized coating. Stays flexible and pliable; lasts many years. It is ideal for a variety of roof surfaces including shingles, metal roofs, chimneys, skylights, gutters, pipes and many other surfaces.

Packing Sizes: 400ml

Kerol Universal Stainer

Kerol Universal stainer is a high strength Gloss Concerntrate used to tint base paints to desired shade. These stainers can tint plastic emulsion, distemper, synthetic enamels and satin paints, However they are not recomded for epoxy polyurethane, chrolinated rubber paints.

Kerol Stainer is available in a range of eleven attraction colours. Shade prepared from stainers yellow, green, red and violet.

Coverage: Not Applicable

Packing Sizes: 50ml, 100ml, 200ml





Kerol Machine Colourant

Kerol Machine Colourant is concetrated pigment dispersion, in aqueous solution, binder free, without alkyl phenol-ethoxylates (APEO-Free). Kerol Machine Colourant is a fluid, ready to use paste with machine dispensing consistency (both volumetric and gravimetric), specifically designed for the tinting of water and solvent based architectural coatings. The product has good light and weathering resistance with a complete selection of colourant for both interior and exterior use.

Coverage: Not Applicable

Packing Sizes: 1Ltr.

Kerol Rapid Plus Enamel

Kerol Rapid Plus Enamel paint has high adherence as their made from oil. It can provide high Gloss and for long time. Syenthetic enamel paint can offer glossy as well as matt finish.

Areas where it can be applied - Wood, Iron, Plaster Surface,

Packing Sizes: 500ml, 1Ltr, 4Ltr, 20Ltr.





Kerol

Enamels / Premium Enamels / Epoxy Paints / P. U. Paints / Hammertones / Poly Chromatic Finish / Red Oxide Primers / Zinc Chrome Primers / F. D. Black / Ganpati Clear Varnish.

Packing Sizes: 200ml, 500ml, 1Ltr, 4Ltr, 20Ltr.

Flexiguard Crack Seal

Kerol Flexiguard Crack Seal is a fiberglass reinforced ready to use crack filling compound for interior and exterior surface.

Ensure that the surface is free from oil, dust, grease, loose, particles, etc.

Widen the crack to form a 'V' grove and prime the surface.

For interior cracks, use Kerol Flexiguard Interior Wall Primer and for exterior cracks use Kerol Flexiguard Exterior Wall Primer

Apply the Kerol Flexiguard Cracl Seal exceding 3 cm from each side of the crack. Press the Paste firmly into the crack with a spatula or putty Knife and level with the surface. These must be applied in Consecutive Perpendicular layers to avoid leaving air pockets.

All to set for 12 hrs before applying the second coat.

Further finishing the POP or Putty can be taken up once the coat if fully dry.



Packing Size: 350 Grams, 1kg, 5kg



Branch Office Indore: 48-A, Udyog Nagar, Palda, Indore - 452020. E-mail: kerolpaintsmp@gmail.com Branch Office Pune: Gurudev Ware Housing, Milkat No. 00554. Sr. No. 163/8+9+10, Lane No. 3, Ramchandra Anna Harpale Nagar, Fursungi Village Road, Fursungi, Pune - 412308. E-mail: kerolpaintspune@gmail.com

Branch Office Kolhapur: CNF Agent Shreepati Enterprise, Plot No. 3/2, Masute Mala, Gandhi Nagar Road, Kolhapur-0231-2610022 • Tel.: 8956428137 / 7058016155